You are browsing the product catalog for United States

ML6421 Series 1800N Linear Valve Actuators

ML6421 series linear valve actuators are used with control valves in sizes ranging from DN15 to DN150 connection size, with 20mm and 38mm stroke. They are used in a variety of applications where control accuracy is critical.

Overview



ML6421 series provide 3-P floating control of 20mm and 38mm stroke control valves. The actuators are used with threaded valves in the V5011 and V5013 series, and flanged valves in the V5015, V5016, V5025, V5049, V5050, V5328, and V5329 series.

Varieties include 24Vac and 230Vac power, manual operation, 108s or 210s runtime (for 20mm and 38mm stroke respectively). Visual position indication available on the actuator yoke. Actuators are rated at 1800N linear force and IP54 protection class. Accessories are available separately, such as high temperature kits, auxiliary switches, and feedback modules.

Please sign in to purchase. Sign In

3 Skus

Search by Part Number or Description Clear

Compare	Part Number		Description
☐	ML6421B3004		3-Point Linear Valve Actuator, 24Vac, 38mm stroke, 1800N, 210s
☐	ML6421A3005		3-Point Linear Valve Actuator, 24Vac, 20mm stroke, 1800N, 108s
☐	ML6421A3005/U	Discontinued	Valve Actuator

Related Products



V5015/V5329C 3-Way Flanged Large Linear...

Linear Control Valves are used for heating and air conditioning in

LEARN MORE

V5328 Series 2-Way Flanged Large Linear...

The 2-way Linear Valves are used for flanged connections for

LEARN MORE

V5025 Series 2-Way Flanged Pressure...

The V5025A Flanged Linear valves are suitable for use in

LEARN MORE